



APPLICATION

- Silicone hose for delivery of high purity products, foodstuff and fluids with alcohol content up to 96%.
- Normally used in food, pharmaceutical and cosmetic industries.

CONSTRUCTION

TUBE

- Silicone rubber, translucent (code SILICONE-3362PT), food and pharmaceutical quality, odourless and tasteless, smooth, glossy finish.

REINFORCEMENT

- High strength polyester plies.

COVER

- Silicone rubber, translucent (code SILICONE-3362PT), food and pharmaceutical quality, odourless and tasteless. Smooth with glossy finish.
- It may easily be washed with any mild detergents.

STANDARDS

- US Pharmacopoeia Class VI, non-cytotoxic acc. to ISO 10993-Part 5.
- Compliance: 3A, FDA, BfR, E.P. 3.1.9. (European Pharmacopoeia), ISO 10993-4, -10, -11.

SAFETY FACTOR

- ≥ 4 times working pressure.S

MAIN BENEFITS

- Platinum-cured silicone hose with non-stick and hydrophobic properties.
- Safe solution for use in the aseptic environments and hygienic applications: utmost care is used starting from the choice of high-purity ingredients, production and storing procedures.
- Pharma grade validation: the Clearway design is tested in accordance with USP Class VI, EU Pharmacopoeia and FDA Standards.
- Hose in accordance with EC 1935/2004 and 2023/2006/EC (GMP).
- Our production cycle is free from animal derived ingredients, phthalates, adipates and materials subject to restrictions acc. to EC 1907/2006 (REACH).
- Plasticizers free hose.
- Nitrosamines free hose.

TEMPERATURE RANGE

- From -60°C to +200°C.

STERILIZATION

- Sterilization with steam up to +135°C , at 3.5 bar for max 90 minutes.
- Sterilization with hot air up to +200°C for max 30 minutes.
- Sterilizations repeated at intervals of less than 1 hour may seriously affect the mechanical features of the hose.

TECHNICAL SPECIFICATIONS

SIZE TOLERANCES: I.D.: ISO 1307 - Wall thickness: +1/-0.5mm - Length: ISO 1307

Inner Diameter mm	Outer diameter mm	Wall thickness mm	Working pressure* BAR	Burst pressure BAR	Min. bending radius mm	Vacuum BAR	Approx. weight kg/m	Max. length m
13	24	5.5	10	40	-	-	0.374	20
19	30	5.5	10	40	-	-	0.490	20
25	37	6.0	10	40	-	-	0.602	20
38	49	5.5	10	40	-	-	0.862	20
51	62	5.5	7	28	-	-	1.222	20

(*) At a temperature of +100°C the W.P. decreases by 20%.
Above technical data refer to application at room temperature $\leq +20^\circ$
Other sizes are available upon request. Please contact our Sales Department.



Neel Industrial Solutions

Plot No. X / 12, Office No.5, Onkar Premises Society ,
Near Thakur Hospital, MIDC, Dombivli (E) 421 203.

☎ 98339 24947 | 98337 88014

✉ bgore@neelpharma.com ✉ marketing@neelpharma.com

🌐 www.neelpharma.com



APPLICATION

- Platinum-cured silicone hose, designed for conveying high-purity products
- It is normally used in the pharmaceutical, cosmetic, biotech and food industry.
- Delivery hose, not recommended for suction.
- Hose in accordance with EC 1935/2004.
- Autoclavable.

CONSTRUCTION

TUBE

- Platinum-cured silicone rubber, pharmaceutical and food quality, light colour, odourless and tasteless, mirror smooth.

REINFORCEMENT

- Plies of synthetic cord.

COVER

- Platinum-cured silicone rubber, pharmaceutical and food quality, light colour, odourless and tasteless, mirror smooth.

STANDARDS

- Tube and cover: USP Class VI, 3A, FDA Standards, European Pharmacopoeia (E.P. 3.1.9.), BfR Recommendation XV, ISO 10993-4, -11, non-cytotoxic according to ISO 10993-Part 5.

MAIN BENEFITS

- Non-stick hose: it provides utmost safety during transport of high-purity fluids, thus removing the risk of bacterial growth on the hose surfaces.
- Perfectly smooth: it may easily be cleaned.
- Translucent, platinum-cured silicone: the see-through material is important for liquid-handling applications where the flow must be monitored.
- Non-plasticized hose.

TEMPERATURE RANGE

- From -60°C to +180°C depending on the fluids conveyed.

TEMPERATURE RANGE

- From -60°C to +180°C depending on the fluids conveyed.

SAFETY FACTOR

- ≥ 3 times working pressure.

FITTING

- By means of clamps, collars or crimping.
- If required, we can supply special reusable fittings ensuring a regular flow and preventing turbulences inside the hose.

TECHNICAL SPECIFICATIONS

SIZE TOLERANCES: I.D.: ISO 1307 - Wall thickness: DIN 7715 T4 S2 - Length: ISO 1307

Inner Diameter mm	Outer diameter mm	Wall thickness mm	Working pressure BAR	Burst pressure BAR	Min. bending radius mm	Vacuum BAR	Approx. weight kg/m	Max. length m
3.18	9.81	-	15	45	30	-	70	25
4.72	11.35	-	15	45	35	-	106	25
6.35	13.03	-	15	45	40	-	124	25
7.93	14.61	-	12	36	45	-	147	25
9.52	16.32	-	12	36	50	-	175	25
12.70	20.10	-	10	30	65	-	237	25
15.87	24.37	-	8	24	75	-	330	25
19.05	27.91	-	8	24	80	-	415	25
22.20	31.12	-	5	15	100	-	455	25
25.40	34.50	-	5	15	120	-	513	10
31.75	40.80	-	4	12	150	-	617	10

Chemical resistance acc. to Chemical Resistance Chart. Above technical data refer to application at room temperature (+20°C). Other sizes and colours are available upon request. Please contact our Sales Department.



Neel Industrial Solutions

Plot No. X / 12, Office No.5, Onkar Premises Society, Near Thakur Hospital, MIDC, Dombivli (E) 421 203.

☎ 98339 24947 | 98337 88014

✉ bgore@neelpharma.com ✉ marketing@neelpharma.com

🌐 www.neelpharma.com